



COATINGS TECHNOLOGY (PTY) LTD

Re-Tek Power House
Hv/Cnr Jenner & Lister Str/St
Vanderbijlpark, 1911

Posbus / PO Box 1576
Vanderbijlpark, 1900

Tel no: (016) 981-0107 / (016) 981-0146
(016) 933-8431 / (016) 933-3836

Faks/Fax no: (016) 933-4906

0001

RETEK ACRYLIC ROOF PAINT

Retek Acrylic Roof Paint is an extremely durable coating that is based upon an idea originally developed by researchers at the National Building Research Institute of the CSIR in 1957. This type of acrylic roof coating has proven itself over a period of more than 30 years under the harshest exposure conditions on some of the most difficult to paint surfaces

Roof Paint exhibits the following features:

- Excellent adhesion on clean galvanised steel roofing sheets
- Can also be used on asbestos cement roofing sheets and clay and cement tiles (correct pre-treatment is required)
- It comes in an existing range of colours
- It has superior hiding power
- It is mould and water resistant and will not blister if used correctly
- It contains no harmful agents
- It has an agreeable odour on application which will disappear in a short period of time
- It is manufactured from a high quality emulsion that has high extendibility
- Water based, so cleaning of equipment is a feast
- Only requires one or two coats on most surfaces
- Can easily be overcoated

Roof Paint can be used on the following surfaces:

- Galvanised steel roofing
- Cement-based roofing tiles
- Asbestos cement roofing
- Previously painted surfaces (pre-treatment might be required, depending on the surface)
- Painted galvanised steel roofing tiles

Application procedures

- Clean all surfaces from dust, oil or other contaminants
- Roofs should be not too cold or too hot. (to achieve this they can be wetted with a fine water spray and the first coat of paint applied while still damp)

- Roof Paint can be applied by roller, brush or roller
- Stir thoroughly before use
- Apply one or two coats of Roof Paint, allowing a drying time of about two hours between coats
- As this material is very easy to apply, care should be taken not to overspread
- After application, the equipment and any spillage can be cleaned with water and soap followed by thorough rinsing with clean water

Maintenance of painted surfaces

- Surfaces that have been coated with Roof Paint are very easy to maintain – Just wash with an ordinary household cleaner or soft soap by using cloth and it will be restored to it's original pristine condition

Product information

Roof Paint is supplied in 1,5 and 20 litre containers

A wide range of colours is available

It has a spreading rate of 10-12 Metres² per litre (depending on colour)