



RETEK COATINGS TECHNOLOGY (PTY) LTD

*Re-Tek Power House
Hv/Cnr Jenner & Lister Str/St
Vanderbijlpark, 1911*

*Posbus / PO Box 1576
Vanderbijlpark, 1900*

*Tel no: (016) 981-0107 / (016) 981-0146
(016) 933-8431 / (016) 933-3836*

Faks/Fax no: (016) 933-4906

0002

RETEK ALL WEATHER ACRYLIC EXTERIOR TEXTURED COATING

All weather is an extremely durable, flexible exterior coating that is based on a superior quality acrylic emulsion. It has been formulated to provide excellent durability, even under extreme weather conditions. When used in the correct manner it provide an attractive finish to the exterior of the building that will bridge hailline cracks with a minimum of chalking and it is also resistant to dirt pickup and staining.

Due to it's textured finish it will also hide blemishes on the substrate it is applied to.

All Weather exhibits the following features:

- Textured finish
- It is resistant to rain and sun even after years of exposure
- It is resistant to flaking when applied in the correct manner
- It can be washed with a soft bristle brush, using soft soap and water
- It comes in an existing range of colours
- It has superior hiding power
- It is mould and water resistant and will not blister if used correctly
- It contains no harmful agents
- It has an agreeable odour on application which will disappear in a short period of time
- It is manufactured from a high quality acrylic emulsion that has high extensibility
- Excellent adhesion
- Water based, so cleaning of equipment is a feast
- Only requires one or two coats on most surfaces and does not need any undercoat?
- Can easily be over coated

All Weather can be used on the following surfaces:

- Brick
- Cement plastered walls
- Gypsum based plaster and gypsum board
- Wood and wood-based products
- Previously painted surfaces (pre-treatment might be required, depending on the surface)

Application procedures

- Clean all surfaces from dust, oil or other contaminants
- Defects can be filled with an appropriate filler
- All Weather can be applied by roller or brush
- Stir thoroughly before use
- Apply one or two coats of All Weather, allowing a dry time of about two hours between coats.
- As this material is very easy to apply, care should be taken not to overspread
- After application, the equipment and any spillage can be cleaned with water and soap followed by thorough rinsing with clean water.
- On porous surfaces the first coat can be thinned with water (20%) or otherwise the surface can be wetted by means of fine water spray and the coating applied while still damp

Maintenance of All Weather painted surfaces

Surfaces that have been coated with All Weather are very easy to maintain – Just wash with an ordinary household cleaner or soft soap by using a soft bristle brush and it will be resorted to its original pristine condition.

Product information

All Weather is supplied in 1,5 and 20 litre containers

A wide range of colours is available

It has a spreading rate of 8-9 Mertes² per litre (this is due to it's textured nature)